

Model Name
Monitored PDU

Model Number
MRV-1623K-12N1



Meter True RMS Current Meter,

Power Monitor Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

Protocols TCP/IP, SNMP, DHCP, UDP

Alarm Thresholds User-Defined Alarm Thresholds for Warning and Overload

Event Alert Email, Trap, Audible Alarm

General

Output	(12) IEC 320 C13
Input	(1) Attached IEC320 C20 Power Cord 3 Meters long
Protection	(1) 16 AMP Circuit Breaker

Communication

DHCP Indication	(1) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-5% +/-0.1AMP

Operation

Nominal Voltage	230V
Voltage	200V ~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	44 x 44 x 700 mm
Weight	2.5 kg

Regulatory Approvals

CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
FCC Part 15 Class A, ICES-003

