

Overview & Features

BRAVO
PDU

Model Name Switched PDU
Model Number SWH-1023J-08N1



Features

Current Meter	Digital True RMS Current Meter
Power Monitor	Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
Protocols	Http, Https, SNMP, DHCP, UDP
Outlet Control	Individual Outlet Control
Power Delay	Power On/Off Sequence can be Defined
Alarm Thresholds	User-Defined Alarm Thresholds for Warning and Overload
Event Alert	Email, Trap, Audible Alarm



Specification

General

Output	(8) IEC320 C13
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C14 Power Cord 3 Meters long
Protection	(1) 10 AMP Circuit Breaker

Communication

SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Network	(1) RJ45 for Ethernet

Current Meter 3 Digits Seven Segments for True RMS Meter
Range: 0A ~ 20 A
Resolution: 0.1A
Precision: +/-2%+/-0.1AMP

Operation

Nominal Voltage 230V
Voltage 200V~ 240V full range
Frequency 50/60HZ full range
Max. Output Current 10 Amp
Temperature 0 ~ 40 Celsius degree
Humidity 0% ~ 90%
Size 90 x 432 x 44 mm
Weight 3 kg

Regulatory Approvals

CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
C-Tick AS/NZS CISPR 22: 2006
FCC Part 15 Class A, ICES-003

