

AS5712-54X

10GbE Data Center Switch

Bare-Metal Hardware

First Switch Design Approved by Open Compute Project



Product Overview

The Edge-Core AS5712-54X switch meets the high-performance, availability, and network-scaling requirements of enterprise and cloud data centers. The AS5712-54X provides full line-rate switching at Layer 2 or Layer 3 across 48 x 10GbE ports and 6 x 40GbE uplinks. The switch can be deployed either as a Top-of-Rack switch, or as part of a 10GbE or 40GbE distributed spine, forming a non-blocking folded CLOS data center fabric. The switch is rack mountable in either a standard 19 inch rack, or with the Open Rack Switch Adapter in the 21 inch Open Rack.

The AS5712-54X hardware provides the high availability features required for data center operation, including; redundant, hot-swappable AC or -48VDC PSUs or 12VDC power input; fan tray with 4+1 redundant fans; and port-to-power or power-to-port airflow options. The AS5710-54X is an ideal Top-of-Rack switch for virtualized data centers, with its support of VXLAN and NVGRE tunneling functions in hardware.

Key Features and Benefits

- Cost-effective, bare-metal switch infrastructure for data center fabric.
- 48 x SFP+ switch ports, supporting 10GbE (DAC, 10GBASE-SR/LR) or 1GbE (1000BASE-T/SX/LX).
- 6 x 40 QSFP switch ports, each supporting 40GbE (DAC, 40GBASE-SR4/LR4) or 4 x 10GbE (DAC or fiber breakout cable).
- Port Grouping to group 4 x 10G ports into one 40G port at the physical layer for maximum bandwidth utilization, and for 300m optical reach over MMF.
- Full line-rate Layer 2 or Layer 3 forwarding of 1.44Tbps.
- VXLAN and NVGRE tunneling support in hardware for network virtualization.
- Rack mountable in standard 19" racks. Mountable in 21" Open Rack with the Open Rack Switch Adapter.
- Supports hot/cold aisle with port-to-power and power-to-port airflow SKUs.
- All ports on front; PSUs, fan tray on rear.
- Hot-swappable, load sharing, redundant AC or -48VDC PSUs. 12VDC power input option.
- Hot swappable 4+1 redundant fans.
- Management: Ethernet and console RJ-45 ports; USB storage port.
- Hardware switch pre-loaded with Open Network Install Environment (ONIE) for automated loading of compatible NOS software. Compatible with Open Network Linux, an open-source, OCP-approved reference NOS.
- Compatible with Cumulus® Linux® r2.5.1 and later SwitchOS software from Cumulus Networks™.
- Compatible with Switch Light OS from Big Switch Networks.
- CPU and memory subsystem provided on factory-pluggable internal module for flexibility
 - AS5712-54X SKUs with Intel™ Atom® C2538 x86 processor



Cumulus® Linux®
Ready

Features

Ports

Switch Ports:
48 x SFP+ each supporting 10GbE or 1GbE
6 x QSFP each supporting 40GbE or 4 x 10GbE
Management Ports on Front Panel:
1 x RJ-45 serial console
1 x RJ-45 100/1000BASE-T management
1 x USB Type A storage port

Key Components

Switch Silicon: Broadcom BCM56854 Trident II 720Gbps CPU
CPU Modules: Intel Atom C2538 quad-core 2.4GHz x86 processor
8GB SO-DIMM DDR3 RAM with ECC
16MB SPI
8GB NAND

Performance

Wire Speed Forwarding: L2 and L3
Switching Capacity: 1.44Tbps
Forwarding Rate: 1Bpps
MAC Addresses: 320K
VLAN IDs: 4K
Jumbo frames (9216Bytes)
L3 Routes: IPv4 64K, IPv6 20K
Packet Buffer Size: 12MB shared buffer pool
Latency (RFC2544): 720 ns (L2/L3, cut thru, full line rate)

LEDs

10G SFP+ Port LEDs: Link Speed, Link Status, Activity
40G QSFP Port LEDs: Link Status, Activity for 40G status
40G QSFP Breakout LEDs: set of 24 LEDs, 4 per QSFP port, show Link, Status, Activity 10G links with 4x10G breakout
Ethernet Management Port LED: Link Status, Activity
Console Port LED: Link Status
System LEDs: PSU1, PSU2, Diagnostic, Fans, Locator

Supported Optics and Cables

SFP+ Ports:
10GBASE-CR DAC: up to 5m passive; up to 10m active
10GBASE-SRL/SR: up to 100/300m over OM3 MMF
10GBASE-LR: Up to 10km over SMF 10GBASE-1000BASE-SX, 1000BASE-LX, 100/1000BASE-T
QSFP Ports:
40GBASE-CR4 DAC; 0.5m to 7m; Passive and Active
40GBASE-CR4 DAC to 4 x SFP+ 10GBASE-CR DAC; up to 5m passive; up to 10m active
40GBASE-SR4: Up to 100m over OM3 MMF, 150m over OM4 MMF
40GBASE-SR4 to 6 x 10GBASE-SR: 100m over OM3, 150m OM4
40GBASE-LR4: Up to 10km over SMF

Software

Open Network Install Environment (ONIE) software installer
Compatible with Open Network Linux, open source reference NOS
Compatible with the Cumulus® Linux® r2.5.1 and later

Physical and Environmental

Dimensions (WxDxH): 443 x 473 x 43.4mm (17.4 x 18.6 x 1.71 in)
Weight: 8.5kg (18.74lbs), with two installed PSU modules
Fans: hot-swappable 4+1 redundant fans
Operating Temperature: 0°C to 40°C (32°F to 104°F)
Storage Temperature: -40°C to 70°C (-40°F to 158°F)
Operating Humidity: 5% to 95% non-condensing

Power

PSUs: 2 redundant, load-sharing, hot-swappable AC or -48VDC
Input Voltage: 90 to 264VAC at 50-60Hz. -48 to -72VDC.
Input Current: Max 6A @100/120VAC, 3A @200/240VAC, 10A @-72VDC
PSU Efficiency: Up to 93% for AC PSUs
12VDC power input option

Regulatory

EMI
CE Mark (EN55022 Class A)
FCC Part 15 Class A
VCCI
Safety
CB, EN 60950
UL/CUL
Environmental: Temperature: IEC 68-2-14
Drop: ISTA 2A
RoHS-6 Compliant
Country of Origin: Taiwan (TAA Compliant)

Warranty

Please check www.edge-core.com.au for the warranty terms in your country. The warranty provides return-to-factory hardware replacement for a three year period in Australia.

For More Information

To find out more about Edge-Core Networks products and solutions, visit www.edge-core.com.au.

About Edge-Core Networks

Edge-Core Networks is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edge-Core Networks delivers the software and systems that transform the way the world connects. Edge-Core Networks serves customers and partners worldwide. Additional information can be found at www.edge-core.com.au.

Edge-Core Networks is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edge-Core data center switches are developed and manufactured by Accton.

To purchase Edge-Core solutions, please contact your Edge-Core Network representatives on 1300 725 323.

© Copyright 2015 Edge-Core Networks Corp. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edge-Core Networks. Edge-Core Networks shall not be liable for technical or editorial errors or omissions contained herein.

Ordering Information

Base Model: AS5712-54X 48-Port 10G SFP+ with 4x40G QSFP uplinks; ONIE software installer				
Model Number	CPU Module	PSU	Airflow	Region (power cord)
5712-54X-O-AC-F-US	Intel Atom C2538 processor	dual AC PSUs	port-to-power airflow	N. America
5712-54X-O-AC-B-US	Intel Atom C2538 processor	dual AC PSUs	power-to-port airflow	N. America
5712-54X-O-AC-F-EU	Intel Atom C2538 processor	dual AC PSUs	port-to-power airflow	Europe
5712-54X-O-AC-B-EU	Intel Atom C2538 processor	dual AC PSUs	power-to-port airflow	Europe
5712-54X-O-AC-F-UK	Intel Atom C2538 processor	dual AC PSUs	port-to-power airflow	UK
5712-54X-O-AC-B-UK	Intel Atom C2538 processor	dual AC PSUs	power-to-port airflow	UK
5712-54X-O-AC-F-JP	Intel Atom C2538 processor	dual AC PSUs	port-to-power airflow	Japan
5712-54X-O-AC-B-JP	Intel Atom C2538 processor	dual AC PSUs	power-to-port airflow	Japan
5712-54X-O-48V-F	Intel Atom C2538 processor	dual 48VDC PSUs	port-to-power airflow	
5712-54X-O-48V-B	Intel Atom C2538 processor	dual 48VDC PSUs	power-to-port airflow	
5712-54X-O-12V-F	Intel Atom C2538 processor	one 12VDC power input	port-to-power airflow	
5712-54X-O-12V-B	Intel Atom C2538 processor	one 12VDC power input	power-to-port airflow	

Model Number	PSU	Airflow	Region (power cord)
PSU-AC-400-F	400W AC Power Supply FRU	port-to-power airflow	no power cord
PSU-AC-400-B	400W AC Power Supply FRU	power-to-port airflow	no power cord
PSU-48V-400-F	400W -48V DC Power Supply FRU	port-to-power airflow	no power cord
PSU-48V-400-B	400W -48V DC Power Supply FRU	power-to-port airflow	no power cord
PSU-12V-400-1	12V DC power input unit FRU		
FAN-1U-1x1D-F	Fan Tray FRU	port-to-power airflow	
FAN-1U-1x1D-B	Fan Tray FRU	power-to-port airflow	

Model Number	Description
CBL-PWR-US	AC Power Cable - US (125V/13A, 1830mm) – only required with spare power supplies
CBL-PWR-EU	AC Power Cable - Europe (250V/10A, 1830mm) – only required with spare power supplies
CBL-PWR-UK	AC Power Cable - UK (250V/10A, 1830mm) – only required with spare power supplies
CBL-PWR-JP	AC Power Cable - Japan – only required with spare power supplies
5712-54X-SVC-RTF	AS5712-54X Annual Hardware Service, post warranty, Return-to-Factory
ORSA-1U	Open Rack Switch Adapter, for mounting standard 19 inch form factor 1U switches into 21 inch Open Rack