




# 5GHz AC867 Wave2 Outdoor Long Range EnJet Wireless Customers Premise Equipment

**The edge 802.11ac built-in high performance CPE with EnJet technology lets client device use predesignated time slots to maximize airtime efficiency**

EnGenius Wireless Long Customers Premise Equipment (CPE) solution is designed for deploying under the pervasive outdoor application. To meet today's requirement on varied networking environment, EnGenius would like to provide the solution as flexible, robust and effective as the organization they desire.

The built-in powerful CPU combines with the state-of-the-art 802.11ac and EnJet technology lets client device use predesignated time slots to maximize airtime efficiency and brings revolutionary connecting speed and bandwidth for diversity of multimedia applications under a pervasive environment. ENS500-ACV2 and ENS500EXT-ACV2 equip with a powerful RF interface which supports up to 867 Mbps in 5GHz frequency band to replace 11N 300Mbps solution. With robust IP55 certified casing, this access point is designed to withstand harsh environment conditions including serve and prolonged exposure to sunlight, extreme cold, frost, snow, rainfall, hail and humidity.



## Features

- > Engineered with powerful CPU and support 11AC Wave2 Performance.
- > 2x2 802.11 ac wave2/a/n Access Point with multi-user MIMO (MU-MIMO)
- > EnJet technology can deliver traffic easy and durable under a pervasive environment.
- > Boost speed up to 867 Mbps air performance in 5GHz frequency band.
- > Engine with 802.11ac Wave2 technology to enhance overall bandwidth and speed to bridge devices.
- > Built-in high gain directional antenna to deliver content to the long-range distance site. (ENS500-ACV2)
- > External antennas interface for connecting with high directional antennas to deliver signal to long-range distance. (ENS500EXT-ACV2)
- > Compliance with Proprietary 24V PoE Input for flexible installation over 100 meters (328 feet).
- > Robust housing with IP55 enclosure rated to deploy at extremely weather .
- > Deliver High resolution content or multiple IP surveillance over wireless transmission

## Wireless Management solution is ideal for deployment in these venues:

- |                        |                      |                       |
|------------------------|----------------------|-----------------------|
| > Airport Terminals    | > Hospital Buildings | > Resort Properties   |
| > Warehouse Operations | > Construction Sites | > Parks & Campgrounds |
| > College Campuses     | > Building Sites     | > Stadiums & Arena    |
| > Corporate Campuses   | > Shopping Malls     | > Public Lightings    |

## Enterprise Robust Solution

ENS500-ACv2 and ENS500EXT-ACv2 is easily to install anywhere and its internal electronics have been mounted in an **IP55-rated** enclosure, one of the better waterproof and dustproof rating available, designed to withstand harsh environment conditions including serve and prolonged exposure to sunlight, extreme cold, frost, snow, rainfall, hail and humidity .

## Scalable and Flexible deployment for Outdoor Installation

With included mounting accessories, ENS500-ACv2 and ENS500EXT-ACv2 provides reliable kits to fix this device on anywhere for delivering wireless signal under outdoor environment. To save the maintenance cost and labors fee on deploying Access Points, these products had been built in two Gigabit Ethernet ports with power over Ethernet (PoE) functions for receiving power source from the included PoE adapter. With scalable extension over PoE mechanism, Access Points can receive power and signal source easily from **100 meters or 328 feet distance**.

Meanwhile, EnGenius ENS500EXT-ACv2 also built in external SMA interfaces for users to connect with other high-gain directional antennas for delivering the wireless signal to long-range distance.


## Provide Consistent Performance

Designed by EnGenius could provide the powerful RF interface to assure the reliability of signal strength and sensitivity in a pervasive environment. These optimist interfaces will provide the evenly coverage to assist users to reduce dead spots in their WLAN and boost received signal quality to deliver the best **867Mbps** air performance to wireless client devices.

## Carry multimedia content over EnJet technology.

The ENS500-ACv2 and ENS500EXT-ACv2 engineered with a breakthrough EnJet technology ,which lets an Access Point to arrange each Customers Premise Equipement (CPE) for sending and receiving data using pre-designated time slots scheduled. This method eliminates hidden node collisions and optimizes airtime efficiency under a pervasive environment. It provides many magnitudes time slot of performance improvements in latency, throughput, and scalability compared to traditionally outdoor Wireless point to point or point to multi-points systems in its class.

In addition, with MU-MIMO and Beamforming technology, ENS500-ACv2 and ENS500EXT-ACv2 outdoor long-range Access Point could bring more traffic to wireless client devices simultaneous and enhances the higher signal-to-noise ratio and greater throughput of that client devices.



## Securable Portals for different purpose

Administrators can also use **Virtual LAN (VLAN)** with **Guest Network** to isolate each client for avoiding an unnecessary touch, leaking sensitive data, and enhancing Internet security and reliability for internal network.

With **VLAN per SSID**, the Integrate VLAN ID with a WLAN service set identifier (SSID) interface will deliver packets to the defined path. The built-in QoS mechanism could allow the specific VLAN SSID to get more bandwidth and deliver video streaming content to the destination first.



## Restrain Wireless Traffic under a Pervasive Environment

To effectively manage the usage of each client device at a LAN topology, **Traffic Shaping** controls the bottle of bandwidth to offer the limited bandwidth for an individual **SSID** or **each client** per Access Point. This constraint offers the constant bandwidth to perform specific applications like VOIP and video streaming fluently and smoothly without air congestion on each client devices.

## Comprehensive Network Protection

With ETD Access Points, your network is protected from attacks at multiple level through advanced wireless encryption standards such as Wi-Fi Protected Access (WPA2) which uses authentication database and IEEE 802.1X with Radius server. EnGenius also offers the advanced encryption standard (AES) to encrypt traffic between Access Points and client devices. To isolate the internal client devices and guest devices, client isolation can avoid each client device to see each other under the same WLAN. Once threats or events are detected, built-in **E-mail Alerts** systems will automatically deliver an e-mail notification for administrators to trigger immediate actions on these networks threats.

## Technical Specifications Wireless outdoor long-range Access Point

### Wireless Radio Specification

#### Access Point Type:

Outdoor, IP55, dual radios concurrent, 5GHz 802.11 ac 2x2 MIMO is backwards compatible with 802.11 ac/a/n mode

#### SU-MIMO:

Two(2) spatial stream SU-MIMO for up to 867 Mbps wireless data rate to a single wireless client device.

#### MU-MIMO

Two(2) spatial stream MU-MIMO for up to 867 Mbps wireless data rate to transmit to two(2) wireless client devices simultaneously.

#### Frequency Radios

5GHz: 5150MHz~5250MHz, 5250MHz~5350MHz, 5470~5725MHz, 5725MHz~5850MHz

Support radios and channels will be varied on the configured regulatory domain.

#### Supported Radio Technology

802.11n/ac: 2x2 MIMO with 2 streams  
802.11ac supports very high throughput (VHT) — VHT 20/40/80 MHz  
802.11n supports high throughput (HT) — HT 20/40 MHz  
802.11n/ac packet aggregation: AMPDU, ASPDU  
Orthogonal frequency-division multiplexing (OFDM) under 802.11ac/a/n  
EnJet technology with Time Division Multiple Access (TDMA) under 802.11ac/n

#### Supported Modulation Type

802.11a/n: BPSK, QPSK, 16-QAM, 64-QAM  
802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM

#### Transmit Power (Maximum Value)

26dBm

Maximum power is limited by regulatory domain

#### Tx Beamforming (TxBF)

Increasing signal reliability and transmitting distance.

#### Supported data rates (Mbps)

802.11a: 6, 9, 12, 18, 24, 36, 48, 54  
802.11n: 6.5 to 300 (MCS0 to MCS15)  
802.11ac: 6.5 to 867 (MCS0 to MCS9, NSS=1 to 2)

### Power

#### Maximum Power Consumption

Maximum 8.93W

#### Power Source

Proprietary 24V PoE (Power: 4, 5; Return: 7, 8)  
Active Ethernet (Power Over Ethernet, PoE)

### Antenna

#### Antenna Types

ENS500-ACv2: High-gain directional 14 dBi Antenna  
ENS500EXT-ACv2: Two(2) detachable 5.0dBi SMA antennas  
Widely frequency supported from 5150MHz to 5925MHz

#### Optional Solutions

Alternative solution to compatible with SA5219 sector Antennas.  
(ENS500EXT-ACv2 Only)

### Interfaces

#### Networking Interface

Two (2) 10/100/1000 BASE-T RJ-45 Ethernet Ports

#### LED Indicators

Display system and wireless transmission status

#### Reset Button

Convert Access Point to the Factory default or the Users Default

### Mounting

#### Pole Mounting

Assemble a mounting bracket to fix this Access Point on a pole.

#### Wall Mounting

Mount this Access Point on a flat wall

### Mechanical & Environment

#### Dimensions (Device only)

186mm (L) x 100mm (W) x 29mm (H) (7.54" x 4.49" x 1.88")

#### Weight

504g (1.11lbs)

#### Operating

Temperature: -20°C~60°C (-4°F~140°F)  
Humidity: 0% ~ 90% typical

#### Storage

Temperature: -40°C~80°C (-22°F~176°F)  
Humidity: 0% ~ 90% typical

#### Environment Protection Level

IP55

#### Surge Protection

Line to Line: 1.0KV  
Line to Ground: 2.0KV

#### ESD Protection

Contact: 4KV  
Air: 8KV

### Compliance Regulatory

#### FCC

Subpart 15 B  
Subpart E 15.407

#### CE

EN 301 893  
EN 301 489-1/-17  
EN 50385  
EN 55032  
EN 55024  
EN 60950-22

#### Electromagnetic Compatibility (2014/30/EU)

#### Low-voltage Directive (RED 2014/35/EU)

## Technical Specifications Wireless outdoor long-range Access Point

### Operating Mode

#### Access Point Mode (AP Mode)

Be an Access Point behaves like a central connection for station or clients that support IEEE 802.11 ac/a/n network.

#### Client Bridge Mode (CB Mode)

The Access Point essentially acts as a wireless adapter that connects to an access point to allow a system of wireless access to the network in the client bridge mode.

#### WDS Modes (WDS AP, WDS Station)

WDS modes uses WDS technology to establish the wireless connection via filling MAC address in both Access Points to enlarge the wireless area.

### Exquisite RF Management

#### ACK timeout (Distance Control)

Set the ACK timeout to assure the proper distance to deliver wireless signal properly

#### Site Survey

Scan signal level of an environment to provide parameters for performing Auto Transmit power and auto channel.

#### Auto Transmit Power

Automatically adjust power level

#### Auto Channel

Automatically assign a clearly channel to perform RF transmission under a pervasive environment.

#### RSSI Threshold

Kick client devices that the signal (RSSI) is above the set value from the AP for reducing the interference and optimize the connecting quality.

### Optimize Performance

#### Quality of Service

Compliance with IEEE 802.11e standard  
Prioritizes voice over data for both tagged and untagged traffic  
Transmit video, voice and data at the same SSID

#### Power Save Mode

Support U-APSD

#### Pre-Authentication

Compliance with 802.11i & 11x

#### PMK Caching

Compliance with 802.11i  
If wireless client devices has authenticated to an access point, it does not perform a full authentication exchange when client devices roaming between access points.

#### Fast Roaming (802.11r)

Use a Fast Transition key to handover between Access Points (ENS500EXT-ACV2)

#### Multicast to Unicast Conversion

Using the IGMP protocol, an access Point delivers high definition content to a large number of clients simultaneously.

### Easy to Management

#### Multiple SSIDs

BSSID support  
EnJet Enable: Support 1 SSID for EnJet linkage and 1 SSID for CSMA client to configure EnJet AP  
EnJet Disable: Support 8 SSIDs for CSMA client

#### Guest Network

Isolate each client for avoiding an unnecessary touch, leaking sensitive data, and enhancing Internet security and reliability.

#### VLAN Tag

Independent VLAN setting can be enable or disable. Any packet that enters the Device without a VLAN tag will have a VLAN tag inserted with a PVID (Ethernet Port VID).

#### VLAN Pass-through

Broadcast VLAN-tag packets to find the destination and deliver packets over the defined path. The functions allows network topology scalable and flexible.

#### VLAN Per SSID

Integrate VLAN ID with a SSID interface to forward packets over the defined path. The functions isolate client devices to get more security.

#### Management VLAN

Feature is enabled with specified VLAN ID, the device will only allow management access with the same specified VLAN ID from remotely location by using protocols such as telnet, SSH, snmp, syslog etc.

#### Traffic Shaping

Controls the bottle of bandwidth to offer the limited bandwidth for an individual SSID or each client per Access Point.

#### MAC Address Filtering

Filter up to 32 sets MAC addresses per SSID

#### E-Mail Alert

Provides a network monitoring tool for administrators to stay informed the configuration change.

#### Save Configuration as Users Default

Save the customized configuration as default value for different customer demands.

#### Wi-Fi Scheduler

Perform a regular reboot on access point at assigned schedule  
Perform it to enable or disable 2.4GHz or 5GHz interface from a period time.

#### SNMP & MIB & CLI

v1/v2c/v3 support  
MIB I/II, Private MIB  
CLI Supported

#### RADIUS Accounting

Help operators to offload 3G to Wi-Fi seamlessly

#### Wireless Clients list

Provide the list to display real status of wireless client devices on this Access Point.

### Comprehensive Protection

#### Wireless Encryption Standard

WPA2-AES PSK  
WPA2 Enterprise

#### Hide SSID in beacons

#### Client Isolation

Block/Isolate the communication between the associated clients under the same WLAN.

#### HTTPS

A secure communication protocol can be enabled to allow secure management web access over a computer network.

#### SSH Tunnel

A secure communication protocol can be enabled to allow secure remote shell access or command execution.

## RF Performance Specification Wireless outdoor long-range Access Point

Channel	Data Rate	Transmit Power (Aggregated, dBm)	Receive Sensitivity (Aggregated, dBm)
802.11b 2.4 GHz	1 Mbps	-	-
	2 Mbps	-	-
	5.5 Mbps	-	-
	11 Mbps	-	-
802.11g 2.4 GHz	6 Mbps	-	-
	54 Mbps	-	-
802.11a 5 GHz	6 Mbps	26.0	-92.0
	54 Mbps	24.0	-75.0
802.11n HT20 2.4 GHz	MCS 0 / 8	-	-
	MCS 7 / 15	-	-
802.11n HT40 2.4 GHz	MCS 0 / 8	-	-
	MCS 7 / 15	-	-
802.11n HT20 5GHz	MCS 0 / 8	26.0	-93.0
	MCS 7 / 15	22.0	-72.0
802.11n HT40 5GHz	MCS 0 / 8	25.0	-90.0
	MCS 7 / 15	22.0	-70.0
802.11ac VHT20 5GHz	MCS0	25.0	-92.0
	MCS9	22.0	-69.0
802.11ac VHT40 5GHz	MCS0	25.0	-90.0
	MCS9	22.0	-65.0
802.11ac VHT80 5GHz	MCS0	25.0	-87.0
	MCS9	21.0	-60.0

\*Maximum RF performance of the hardware provided. Maximum transmit power is limited by local regulatory.


\*The supported frequency bands are restricted by local regulatory requirements.

\*Transmit power is configured in 1.0dBm increments.


# Antennas Patterns Wireless outdoor long-range Access Point

ENS500EXT-ACv2





5GHz H-Plane




5GHz E-Plane




ENS500-ACv2




## Physical Interfaces



External antenna  
(SMA Interface)  
(ENS500EXT-ACV2 Only)



	ENS500-ACv2	ENS500EXT-ACv2
		
<b>Standards</b>	802.11ac/a/n	802.11ac/a/n
<b>Frequency</b>	5150MHz~5850MHz	5150MHz~5850MHz
<b>Data Rates</b>	867 Mbps	867 Mbps
<b>Antennas</b>	Directional 14dBi	External SMA 5dBi
<b>Physical Interface</b>	2 x Gigabit LAN	2 x Gigabit LAN
<b>Radio Chains/Streams</b>	2x2: 2	2x2: 2

\* The supported frequency and maximum Tx power will be varied by the local regulatory.