

Overview & Features



Model Name: POM PDU
Model Number: MSH-1023J-08N8



Description

230V, 10A, 8 Outlets, Remote Per Outlet Monitoring, Remote Power Switch

Features

- Current Meter** Digital True RMS Current Meter
- Power Monitor** **Per Outlet Output Power and Total Power Monitoring** by Meter, Web, SNMP, Free Bundle Software
- Protocols** Http, Https, SNMP, DHCP, UDP
- Outlet Control** Individual, Group, Schedule, Auto Ping
- Power Delay** Power On/Off Sequence can be Defined
- Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload
- Event Alert** Email, Trap, Audible Alarm
- Temp./Humidity** Option Accessory



Specification

General

- Output (8) IEC320 C13
- Input (1) IEC320 C20 Inlet;
Enclosed IEC320 C19 to C14 Power Cord 3 Meters long
- Protection (1) 10 AMP Circuit Breaker

Communication

- SSL Indication (1) Yellow LED

DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Circuit Status	(8) Red LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segments for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2% +/-0.1AMP

Operation

Nominal Input Voltage	230V
Output Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	10 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	160 x 432 x 44.45 mm
Net Weight	3 kg

Regulatory Approvals

CE, CISPER 22, CISPER 24 ,IEC 61000-3-2, IEC 61000-3-3
FCC Part 15 Class A, ICES-003

