

Overview & Features



Model Name: POM PDU
Model Number: MSH-1023J-08N8



Description

230V, 10A, 8 Outlets, Remote Per Outlet Monitoring, Remote Power Switch

Features

Current Meter	Digital True RMS Current Meter
Power Monitor	Per Outlet Output Power and Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
Protocols	Http, Https, SNMP, DHCP, UDP
Outlet Control	Individual, Group, Schedule, Auto Ping
Power Delay	Power On/Off Sequence can be Defined
Alarm Thresholds	User-Defined Alarm Thresholds for Warning and Overload
Event Alert	Email, Trap, Audible Alarm
Temp./Humidity	Option Accessory



Specification

General

Output	(8) IEC320 C13
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C14 Power Cord 3 Meters long
Protection	(1) 10 AMP Circuit Breaker

Communication

SSL Indication	(1) Yellow LED
----------------	----------------

DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Circuit Status	(8) Red LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segments for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2% +/-0.1AMP

Operation

Nominal Input Voltage	230V
Output Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	10 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	160 x 432 x 44.45 mm
Net Weight	3 kg

Regulatory Approvals

CE, CISPER 22, CISPER 24 ,IEC 61000-3-2, IEC 61000-3-3
FCC Part 15 Class A, ICES-003

