

RSP126WA / RPS600WA

Redundant Power Supply



Specifications of RPS126WA

Physical Ports
1 redundant power supply port
Power Delivery
Max, output power: 126W / 12V per port
Device Protection
Thermal Protection Overload Protection
Mechanical
Dimensions: TBD Weight: TBD
Safety
CSA / NRTL (UL1950,CSA 22.2.9.50) TUV / GS (EN60950)
Electromagnetic Compatibility
CE Mark Class B
Environmental Specifications
Temperature: IEC 68-2-14 0 ℃ to 45 ℃ (Standard Operating) -40 ℃ to 70 ℃ (Non-Operating) Humidity: (Non-condensing) Vibration: IEC 68-2-36, IEC 68-2-6
Package Content
1 x RPS126WA 1 x cable 1 x power cord
Support Devices
ES3528M-SFP

Specification of RPS600WA

Physical Ports
4 redundant power supply ports
Power Delivery
Max, output power: 150W / 12V per port
Device Protection
Thermal Protection Overload Protection
Mechanical
Dimensions: 440mm x 325mm x 43.95mm (W x D x H) Weight: 7.38kg
Safety
CSA / NRTL (UL1950,CSA 22.2.9.50) TUV / GS (EN60950)
Electromagnetic Compatibility
CE Mark Class B FCC Class B VCCI Class B CISPR Class B
Environmental Specifications
Temperature: IEC 68-2-14 0 ℃ to 45 ℃ (Standard Operating) -40 ℃ to 70 ℃ (Non-Operating) Humidity: (Non-condensing) Vibration: IEC 68-2-36, IEC 68-2-6
Package Content
1 x RPS600WA 4 x Cable 1 x User Manual 1 x Power Cord 1 x Rack Mount Brackets
Support Devices
ES4524D/ ES4548D/ ES5508/ ES3628EA/ ES4626F/ ES4650F/ ECS4610-26T/ ECS4610-50T/ ES3528S