

RPS900W

Redundant Power Supply



Specifications

Physical Ports

- 1 2R*9P Connector
- 1 DB25 Connector

Power Delivery

- Input: 100-240VAC
- Output: -53.5V/14.3A, +11.3V/10A

Device Protection

- Thermal Protection
- Overload Protection

Mechanical

- Dimensions: 379mm x 168mm x 44mm (W x D x H)
- Weight: 3.9kg

Safety

- CSA: CSA60950-1-07 2ND ed. / UL: UL 60950-1 2ND ed.
- CB (EN 60950-1: 2006+A11:2009)

Electromagnetic Compatibility

- CE Mark Class B
- FCC Class B

Environmental Specifications

- Temperature:
 - IEC 68-2-14
 - 0 °C to 55 °C (Standard Operating)
 - 45 °C to 85 °C (Non-Operating)
- Humidity: (Non-condensing)
- Vibration: IEC 68-2-36, IEC 68-2-6

Package Content

- 1 x RPS900W
- 1 x Cable
- 1 x Power Cord

Support Devices

- ECS4510-28T/ECS4510-28P/ECS4510-28F/ECS4510-52T/ECS4510-52P
- ECS4620-28T/ECS4620-28P/ECS4620-28F/ECS4620-52T/ECS4620-52P